

Yohichi INADA., S.N. 10/723,203  
Page 3

Dkt. 2271/71602

### Listing of Claims

The following listing of claims will replace all prior versions, and listings, of claims in the subject application:

1. (currently amended) An information compression apparatus which compresses information and uses a DCT frequency conversion algorithm, comprising:

a plurality of block registers which store block-based multi-bit quantized data converted from information output from a quantization execution module;

a correction level register which presets a correction level indicating a degree number of data ~~correction~~ corrections and/or modifications;

a first control mechanism which controls operations of said apparatus so as to ~~perform a scanning operation for scanning~~ consider the plurality of block registers in a scan order and a ~~search operation for searching~~ search each block in the scan, according to said scan order, for a valid coefficient; and

a data correction mechanism configured to modify the valid coefficient, found in the search ~~operation~~, to an invalid coefficient based on the correction level preset in the correction level register.

2. (original) The information compression apparatus as defined in claim 1, wherein the valid coefficient is a coefficient having any coding amount except zero.

3. (currently amended) The information compression apparatus as defined in claim 1, wherein said scan order in the scanning operation operations includes an inverse zigzag

Yohichi INADA., S.N. 10/723,203  
Page 4

Dkt. 2271/71602

operation.

4. (previously presented) The information compression apparatus as defined in claim 1, further comprising a second control device configured to receive the multi-bit quantized data output from the quantized execution module before the multi-bit quantized data is transmitted to the plurality of block registers, and after said second control device receives the multi-bit quantized data, cause the first control mechanism to start the search operation.

5. (currently amended) The information compression apparatus as defined in claim 1, wherein the data correction mechanism moves an isolated valid coefficient that is at a first address not adjacent to another valid coefficient containing address ~~containing a valid coefficient~~, to a second address that is adjacent to said another valid coefficient containing address ~~containing a valid coefficient~~, when modifying the valid coefficient to the invalid coefficient based on the correction level causes information deterioration to an extent exceeding a predetermined limit.

6. (currently amended) The information compression apparatus as defined in claim 1, further comprising a block register net configured to perform a logical OR to the coefficients in the block registers connected thereto such that 1 is output when any one of the block registers connected thereto has a valid coefficient, and ~~wherein~~ the first control mechanism cancels its scanning operation remaining operations to consider the block registers in the scan order.

7. (previously presented) The information compression apparatus as defined in claim 6,

Yohichi INADA., S.N. 10/723,203  
Page 5

Dkt. 2271/71602

wherein said apparatus comprises a plurality of said block register net, and a number of the block register nets is equal to a number of frequencies used by the DCT frequency conversion algorithm.

8. (previously presented) The information compression apparatus as defined in claim 7, wherein when a quantization table for quantizing the plurality of block coefficients stored in registers is relatively large, plural block register nets for a high frequency side are connected to each other and a logical OR is performed for the plural block register nets.

9. (original) The information compression apparatus as defined in claim 1, wherein the apparatus uses a Huffman coding method.

10. (original) The information compression apparatus as defined in claim 1, wherein the apparatus uses a JPEG coding method.

11. (original) The information compression apparatus as defined in claim 1, wherein the apparatus uses a sound data coding method.

12. (currently amended) An information compression apparatus which compresses information and uses a DCT frequency conversion algorithm, comprising:

a plurality of block register means for storing block-based multi-bit quantized data converted from the information output from a quantization execution module means;

a correction level register means for presetting a correction level indicating a degree

Yohichi INADA., S.N. 10/723,203  
Page 6

Dkt. 22/1/71602

number of data ~~correction~~ corrections and/or modifications;

a first control means for controlling operations of said apparatus so as to ~~perform a scanning operation for scanning~~ consider the plurality of block register means in a scan order and ~~a search operation for searching~~ search each block ~~in the scan~~, according to said scan order, for a valid coefficient; and

a data correction means for modifying the valid coefficient, found in the search operation, to an invalid coefficient based on the correction level preset in the correction level register means.

13. (original) The information compression apparatus as defined in claim 12, wherein the valid coefficient is a coefficient having any coding amount except 0.

14. (currently amended) The information compression apparatus as defined in claim 12, wherein said scan order in the scanning operation operations includes an inverse zigzag operation.

15. (previously presented) The information compression apparatus as defined in claim 12, further comprising a second control means for receiving the multi-bit quantized data output from the quantized execution module means before the multi-bit quantized data is transmitted to the plurality of block register means, and after said second control device receives the multi-bit quantized data, causing the first control means to start the search operation.

16. (currently amended) The information compression apparatus as defined in claim 12,

Yohichi INADA., S.N. 10/723,203  
Page 7

Dkt. 2271/71602

wherein the data correction means moves an isolated valid coefficient that is at a first address not adjacent to another valid coefficient containing address ~~containing a valid coefficient~~, to a second address that is adjacent to said another valid coefficient containing address ~~containing a valid coefficient~~, when modifying the valid coefficient to the invalid coefficient based on the correction level causes information deterioration to an extent exceeding a predetermined limit.

17. (currently amended) The information compression apparatus as defined in claim 12, further comprising a block register net means for performing a logical OR to the coefficients in the block registers connected thereto such that 1 is output when any one of the block register means connected thereto has a valid coefficient, and wherein the first control means cancels ~~the scanning operation~~ remaining operations to consider the block registers in the scan order.

18. (previously presented) The information compression apparatus as defined in claim 17, wherein said apparatus comprises a plurality of said block register net means, and a number of the block register nets means is equal to a number of frequencies used by the DCT frequency conversion algorithm.

19. (previously presented) The information compression apparatus as defined in claim 17, wherein when a quantization table for quantizing the plurality of block coefficients stored in register means is relatively large, the plural block register net means for a high frequency side are connected to each other and a logical OR is performed for the plural block register net means.

20. (original) The information compression apparatus as defined in claim 12, wherein

Yohichi INADA., S.N. 10/723,203  
Page 8

Dkt. 2271/71602

the apparatus uses a Huffman coding method.

21. (original) The information compression apparatus as defined in claim 12, wherein the apparatus uses a JPEG coding method.

22. (original) The information compression apparatus as defined in claim 12, wherein the apparatus uses a sound data coding method.

23. (currently amended) An information compression method for compressing information and using a DCT frequency conversion algorithm, comprising the steps of:

- (a) presetting a predetermined correction level indicating a degree number of data ~~correction~~ corrections and/or modifications;
- (b) latching quantized data including valid coefficients and invalid coefficients into a block register;
- (c) performing an inverse zigzag scan ~~for scanning the block register~~ to search said quantized data latched in said block register in step (b) to find one or more valid coefficients;
- (d) modifying a valid coefficient found in step (c), to an invalid coefficient;
- (e) counting a number of said valid coefficients found in step (c);
- (f) searching for and finding another valid coefficient, and modifying said another valid coefficient to the invalid coefficient;
- (g) incrementing by one the number of valid coefficients counted in step (e);
- (h) continuing the inverse zigzag scan to search for additional valid coefficients, when the number of valid coefficients is smaller than the correction level in step (a); and

Yohichi INADA., S.N. 10/723,203  
Page 9

Dkt. 2271/71602

(i) transferring the data of the block register to a coding module when the number of valid coefficients reaches the correction level.

24. (currently amended) The information compression method as defined in claim 23, wherein in steps (d) and (f), valid coefficients smaller than a predetermined threshold value are modified to an invalid coefficient.

25. (previously presented) The information compression method as defined in claim 23, further comprising a presearching step for searching the quantized data before step (c).

26. (currently amended) The information compression method as defined in claim 23, further comprising an address moving step for moving addresses of isolated valid coefficients searched such that the isolated valid coefficients are arranged in corresponding adjacent addresses when the information deterioration to an extent exceeds a predetermined limit in the modifying steps (d) and (f), and wherein steps (d) and (f) are canceled instead.

27. (previously presented) The information compression method as defined in claim 23, further comprising a calculating step for calculating a total sum of coefficients of block registers arranged along each scanning line corresponding to one of different frequencies used in the DCT frequency conversion algorithm.

28. (currently amended) The information compression method as defined in claim 27, further comprising a summing up step for summing up a plurality of the total sums calculating

Yohichi INADA., S.N. 10/723,203  
Page 10

Dkt. 2271/71602

calculated by said calculating step.

29. (currently amended) A computer-readable medium tangibly embodying a program ~~of an information compression~~ causing a computer to execute an information compression operation using a DCT frequency conversion algorithm according to a method comprising the steps of:

(a) presetting a predetermined correction level indicating a degree number of data ~~correction~~ corrections and/or modifications;

(b) latching quantized data including valid coefficients and invalid coefficients into a block register;

(c) performing a search in an inverse zigzag scan ~~for scanning the block register to search order of~~ said quantized data latched in said block register in step (b) to find one or more valid coefficients;

(d) modifying a valid coefficient found in step (c), to an invalid coefficient;

(e) counting a number of said valid coefficients found in step (c);

(f) searching for and finding another valid coefficient, and modifying said another valid coefficient to the invalid coefficient;

(g) incrementing by one the number of valid coefficients counted in step (e);

(h) continuing the inverse zigzag scan to search for additional valid coefficients, when the number of valid coefficients is smaller than the correction level in step (a); and

(i) transferring the data of the block register to a coding module when the number of valid coefficients reaches the correction level.



Yohichi INADA., S.N. 10/723,203  
Page 11

Dkt. 2271/71602

30. (currently amended) The computer-readable medium tangibly embodying the program of ~~an information compression~~ as defined in claim 29, wherein in steps (d) and (f), valid coefficients smaller than a predetermined threshold value are modified to an invalid coefficient.

31. (currently amended) The computer-readable medium tangibly embodying the program of ~~an information compression~~ as defined in claim 29, further comprising a presearching step for searching the quantized data in step (c).

32. (currently amended) The computer-readable medium tangibly embodying the program of ~~an information compression~~ as defined in claim 29, further comprising an address moving step for moving addresses of isolated valid coefficients searched such that the isolated valid coefficients are arranged in corresponding adjacent addresses when the information deterioration to an extent exceeds a predetermined limit in the modifying steps, and wherein steps (d) and (f) are canceled instead.

33. (currently amended) The computer-readable medium tangibly embodying the program of ~~an information compression~~ as defined in claim 29, further comprising a calculating step for calculating a total sum of coefficients of block registers arranged along each scanning line corresponding to one of different frequencies used in the DCT frequency conversion algorithm.

34. (currently amended) The computer-readable medium tangibly embodying the program of ~~an information compression~~ as defined in claim 33, further comprising a summing up

Yohichi INADA., S.N. 10/723,203  
Page 12

Dkt. 2271/71602

step for summing up a plurality of the total sums ~~calculating~~ calculated by said calculating step to execute code calculation at an appropriate part of the block register.

35. (currently amended) A computer-readable medium tangibly embodying a program ~~of an information compression~~ causing a computer using a JPEG coding method to execute an information compression operation according to a method comprising the steps of:

- (a) presetting a predetermined correction level indicating a ~~degree~~ number of data ~~correction~~ corrections and/or modifications;
- (b) latching quantized data including valid coefficients and invalid coefficients into a block register;
- (c) performing a search in an inverse zigzag scan ~~for scanning the block register to search order of~~ said quantized data latched in said block register in step (b) to find one or more valid coefficients;
- (d) modifying a valid coefficient found in step (c), to an invalid coefficient;
- (e) counting a number of said valid coefficients found in step (c);
- (f) searching for and finding another valid coefficient, and modifying said another valid coefficient to the invalid coefficient;
- (g) incrementing by one the number of valid coefficients counted in step (e);
- (h) continuing the inverse zigzag scan to search for additional valid coefficients, when the number of valid coefficients is smaller than the correction level in step (a); and
- (i) transferring the data of the block register to a coding module when the number of valid coefficients reaches the correction level.

Yohichi INADA., S.N. 10/723,203  
Page 13

Dkt. 2271/71602

36. (currently amended) A computer-readable medium tangibly embodying a program of an information compression causing a computer using a sound data coding method to execute an information compression operation according to a method comprising the steps of:

- (a) presetting a predetermined correction level indicating a degree number of data ~~correction~~ corrections and/or modifications;
- (b) latching quantized data including valid coefficients and invalid coefficients into a block register;
- (c) performing a search in an inverse zigzag scan ~~for scanning the block register to search order of~~ said quantized data latched in said block register in step (b) to find one or more valid coefficients;
- (d) modifying a valid coefficient found in step (c), to an invalid coefficient;
- (e) counting a number of said valid coefficients found in step (c);
- (f) searching for and finding another valid coefficient, and modifying said another valid coefficient to the invalid coefficient;
- (g) incrementing by one the number of valid coefficients counted in step (e);
- (h) continuing the inverse zigzag scan to search for additional valid coefficients, when the number of valid coefficients is smaller than the correction level in step (a); and
- (i) transferring the data of the block register to a coding module when the number of valid coefficients reaches the correction level.

Claim 37 (canceled).

38. (currently amended) The information compression apparatus as defined in claim 1, wherein said correction level preset by said correction level register corresponds to a setting of a

Yohichi INADA., S.N. 10/723,203  
Page 14

Dkt. 2271/71602

number of permitted data corrections, and valid coefficients in said quantized data stored in said plurality of block registers are modified to invalid coefficients until the number of modifications reaches the correction level preset in the correction level register.